AP9640 UPS Network Management Card 3



O	V	e	rν	Œ.	e١	I

0.101.11011		.≌
Lead time	Usually in Stock	plicat

General

Provided equipment User manual USB cable		
	Provided equipment	

Physical

Depth	11.4 cm	
Height	3.8 cm	
Net weight	0.08 kg	-
Width	12.1 cm	

Conformance

Overview		
Lead time	Usually in Stock	
General		,
Provided equipment	User manual USB cable	
Physical		
Depth	11.4 cm	
Height	3.8 cm	
Net weight	0.08 kg	,
Width	12.1 cm	
Conformance		
Standards	EN 55022 class A EN 55024 ICES-003	
Product certifications	AS/NZS 3548 (C-Tick) class A FCC part 15 class A GOST VCCI class A	
Environmental		
Ambient air temperature for operation	045 °C	
Operating altitude	010000 ft	
Relative humidity	095 %	
Ambient air temperature for storage	-545 °C	
Storage altitude	0.0015240.00 m	
Communications & Management		
Authentication	Radius	

Environmental

Ambient air temperature for operation	045 °C	
Operating altitude	010000 ft	
Relative humidity	095 %	
Ambient air temperature for storage	-545 °C	
Storage altitude	0.0015240.00 m	

Communications & Management

Authentication	Radius	This
Communication network type	RJ45 10/100/1000 Base-T	mer:
Communication port protocol	НТТР	l isclaii

HTTPS
IPv4
IPv6
NTP
SMTP
SNMP v1
SNMP v2c
SNMP v3
SSH v1
SSH v2
SSL
TCP/IP
Telnet

Packing Units

Package 1 Weight	0.34 kg	
Package 1 Height	5.1 cm	
Package 1 width	23.5 cm	
Package 1 Length	15.9 cm	

Contractual warranty

Warranty 2 years repair or replace	
------------------------------------	--