

Product datasheet

Specifications



APC Easy UPS On-Line, 6kVA/6kW, Rackmount 5U, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended Runtime, W/O rail kit

SRV6KRIL-IN

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	6000 W
Rated power in VA	6000 VA
Output connector type	Hard wire 3-wire (1P + N + E) 1
Number of rack unit	5U

General

Max runtime	6 min
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black (RAL 7010)
Height	21.95 cm
Width	43.8 cm
Depth	61.5 cm
Net weight	78 kg
Mounting location	Front
Mounting preference	Lower

Mounting mode	Rack-mounted with kit
USB compatible	No
Mounting position	Horizontal

Input

Switching current capacity	50 A
Input voltage limits	110...300 V 60 % load 176...300 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	6000 VA
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	1 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	94 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	BIS
-------------------------------	-----

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...60 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	60 dBA
Heat dissipation	1172 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	240 V
Extended runtime	1
Number of battery filled slots	1
Number of battery free slots	0

Battery recharge time	5 h
Battery charger power	1170 W rated
Battery option	SRV240RBP-9A 1 3024 VAh SRV240RBP-9A 2 4536 VAh SRV240RBP-9A 3 6048 VAh SRV240RBP-9A 4 7560 VAh

Communications & Management

Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes
Control panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49 cm
Package 1 Width	87 cm
Package 1 Length	60 cm
Package 1 Weight	88 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)