

Product data sheet

Specifications



APC NetShelter Basic Rack PDU, 0U, 1PH, 3.3kW, 100-240V 20A or 200-240V 16A, x13 C13 outlets, C20 inlet

AP6020A

Overview

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (13) C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead time	Usually in Stock

Main

Main Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Provided equipment	Installation guide Safety guide

Physical

Colour	Black
Height	38.8 cm
Width	4.4 cm
Depth	9.3 cm
Net weight	1.5 kg
Mounting location	Front Rear
Mounting preference	Lower
Mounting mode	Not rack-mountable
USB compatible	No

Input

[In] rated current	16 A
Permissible voltage	100...240 V
Max line current	20 A
Input current limits	20 A

Load capacity	3300 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	13 IEC 60320 C13
--------------------------------	------------------

Conformance

Product certifications	cUL listed CE EAC IRAM PSE UL listed VDE
------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.6 cm
Package 1 Width	7.6 cm
Package 1 Length	21 cm
Package 1 Weight	2.02 kg
SCC14	10731304327803

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)