

Product datasheet

Specifications



APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord

AP9565

⚠ Discontinued on: 01 November 2020

⚠ Discontinued

Overview

Presentation Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (12)C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

Lead time Usually in Stock

Main

Main Input Voltage 200 V
208 V
230 V

Main Output Voltage 208 V
230 V

Input Connection Type IEC 60320 C20

Number of rack unit 1U

Cable length 2.50 m

Number of cables 1

Provided equipment Installation guide
Rack mounting brackets

Physical

Colour Black

Height 4.4 cm

Width 44.7 cm

Depth 5.7 cm

Net weight 2.05 kg

Mounting location Front
Rear

Mounting preference No preference

Mounting mode Rack-mounted

Input

Input current limits 16 A

Load capacity 3680 VA

Network frequency	50/60 Hz
-------------------	----------

Output

Number of power socket outlets	12 IEC 60320 C13
--------------------------------	------------------

Conformance

Product certifications	cUL listed CE Queensland Australia UL listed VDE
------------------------	--

Standards	UL 60950
-----------	----------

Environmental

Ambient air temperature for operation	0...45 °C
---------------------------------------	-----------

Relative humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	7 cm
------------------	------

Package 1 Width	46.4 cm
-----------------	---------

Package 1 Length	22.9 cm
------------------	---------

Package 1 Weight	3.632 kg
------------------	----------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Lead free	Yes
-----------	-----

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

Take-back	Take-back program available
-----------	-----------------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)