



Price* : 847.00 USD



Overview

Lead time Usually Ships within 2 Weeks

General

| | |
|-------------------------------------|---|
| Provided equipment | CD with software Documentation CD USB cable |
| Product web sub-family | Entry level |
| Performance multiplier | 1 |
| Number of tare power | 24 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |
| Size UPS version | Internetworking Server Telecom |
| UPS size | S |
| Value multiplier | 5 |

Physical

| | |
|---------------------|--------------------|
| Number of rack unit | 0U |
| Colour | Black |
| Depth | 44 cm |
| Height | 21.6 cm |
| Mounting location | Front |
| Mounting preference | No preference |
| Net weight | 27.5 kg |
| Mounting mode | Not rack-mountable |

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Apr 8, 2021

| | |
|--------------------|-------|
| Two post mountable | 0 |
| USB compatible | Yes |
| Width | 17 cm |

Input

| | |
|----------------------|---------------------------------------|
| Network frequency | 47...63 Hz |
| Plug standard | IEC 320 C20 |
| Input voltage limits | 170...300 V adjustable 180...287 V |
| Inputvolt_other | 220 V 240 V |
| Input voltage | 230 V |

Output

| | |
|----------------------------------|--------------------------------|
| Rated power in W | 1300 W |
| Maximum configurable power in W | 1300 W |
| Harmonic distortion | Less than 5 % at full load |
| Output frequency | 50 Hz sync to mains |
| UPS type | Line interactive |
| Wave type | Sine wave |
| Nb of power socket outlets | 6 IEC 320 C13 1 IEC 320 C19 |
| Graph display | 1 |
| Output voltage | 230 V |
| Maximum configurable power in VA | 2000 VA |
| Rated power in VA | 2000 VA |

Conformance

| | |
|-----------------------------|--|
| Product certifications | C-Tick CE EAC GOST SABS VDE |
| Equipment protection policy | 3 years : \$250 |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 45 dBA |
| Heat dissipation | 135 Btu/h |
| Show note OP temperature | No |

Batteries & Runtime

| | |
|--|-------------------|
| Battery type | Lead-acid battery |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |
| Number of battery replacement quantity | 1 |

| | |
|-----------------------|-----------------|
| Liquid value | 0 |
| Battery curve | A |
| Battery charger power | 166 W rated |
| Battery power in VAH | 499 VAh runtime |
| Battery life | 3...5 year(s) |
| Extended runtime | 0 |

Communications & Management

| | |
|---------------|---|
| Free slots | 0 |
| Control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |

Surge Protection and Filtering

| | |
|-------------------|--|
| Surge energy rate | 300 J |
| Noise suppression | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

Packing Units

| | |
|------------------------------|-------|
| Package 1 Weight | 30 kg |
| Package 1 Height | 33 cm |
| Package 1 width | 37 cm |
| Package 1 Length | 59 cm |
| Number of Units in Package 3 | 24 |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|